

RhinoPro HP-11

MACHINE SPECIFICATIONS (High Pressure / High Flow)



- Max Output:** 8 kg/min @ spray tip
Max operating Pressure: 3500psi
Air Requirements:
10ltr/sec @ 7 Bar
(30 CFM at working press 100 psi)
Electrical: 415V, 3PH, 32A
Weight: 200 kg
Dimensions: 790 x 815 x 1179mm
Heated Hose Length: 18m
including 3m whip with digital control.
Heating Power: 15.3kW with individual controls.
Flush kit: Gun Flush kit provided
Air Dryer: RhinoPro 3 stage self-relieving Membrane Dryer
Ratio: 1:1

The RhinoPro HP-11 is a high performance electric DC plural component spray machine specially designed to process Rhino Linings protective lining systems. It is capable of generating 3,500 psi static pressure to accurately mix and spray fast-setting systems. The RhinoPro HP-11 offers a number of advantages including:-

- On/Off trigger capability allows the ability to spray small or intricate parts or thinner coats.
- Ability to control output and spray pattern with various spray tip configurations.
- Compact, portable wheeled cart allows you to move the unit closer to the job and occupies less space.
- Primary heaters allowing for quick startup times with both Polyurethane/Polyurea systems.
- Easy to use Fusion spray gun offers superior mix quality, less maintenance and downtime, easy clean-up and longer component life.
- Pressure Balancing Valves that offer quick and easy balancing of system pressures and recirculation.